

## **Product Information Declaration**

## **Shaw Contract Installation Range**

### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the accessories range sold by Jacobsen as **Shaw Contract Installation** 

### **Identifiers**

See individual sku codes under identifiers

### **Scope and Limitations of Intended Use**

X	Residential	X	Con
×	High Traffic	×	Low
×	Antistatic Environment	×	Food

v Traffic Food Prep Areas X Interior **Exposed Sunlight** Clean Room

Exterior Wet Areas With Wheels

X Ramp/Entry

X Under Floor Heating

Over Existing Floor

### **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	-
Residential	-
Commercial	-
Industrial	-

### **Protection from Fire**

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	-

### **Access**

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	-
Suitable for food prep	-

### **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

### Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	-
	-
	Phthalate-free
Indoor Air Quality	-

### **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## Н

### **Energy Efficiency**

Relevant NZBC Clause **Product Performance** Thermal Rating



### **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

## **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:290424

# **Product Information Declaration Shaw Contract Installation Range**

### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

### D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

### (b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55

### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Note**

It is expected that **Shaw Contract Installation** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:290424

# **Product Information Declaration Shaw Contract Installation Range**

### **Identifiers**

This JPID covers all colours from Shaw Contract Installation including:

Lokworx ELOKWORX Lok Dots Applicator 12731 Shaw LokWorx 3800 Adhesive 15L 12730

Shaw Moisture Impervious Seam Sealer 8300 12742 Shaw Lok Dots Adhesive Sleeve of 8 rolls 12732 Shaw Adhesive Lokworx+Carpet Tile 15L Adhesive 19159

## **Jacobsen**<sup>®</sup>

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328

# **ShawContract®**

Product Manufacturer: Shaw Contract Country of Origin: -

Page 3 of 3