## **Product Information Declaration**

## **Shaw Contract Color Frame Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the carpet range sold by Jacobsen as Shaw Contract Color Frame

#### **Identifiers**

X Over Existing Floor

See individual sku codes under identifiers

#### **Scope and Limitations of Intended Use**

×	Residential	<u> </u>	Commercial	<b>~</b>	Interior	×	Exterior
/	High Traffic	×	<del>Low Traffic</del>	~	Exposed Sunlight	×	<del>Wet Areas</del>
×	Antistatic Environment	×	Food Prep Areas	×	Glean Room	<b>✓</b>	With Wheels

#### R

#### **Stability**

X Ramp/Entry

Relevant NZBC Clause	Product Performance
B2.3.1(c)	Lifetime Commercial Limited
Residential	-
Commercial	Heavy Duty
Industrial	-

## C

X Under Floor Heating

#### **Protection from Fire**

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CHF 8.1 kW/m2 (ISO 9239.1:2010)

## D

#### Access

Relevant NZBC Clause	Product Performance		
D1.3.3			
Level Surface (Wet)	-		
Level Surface (Dry)	Acceptable Solution		
Suitable for food prep	-		

#### F

#### Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	_

## F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	<0.5 mg/m3
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

## G

## **Services and Facilities**

Water resistant
-

## Н

## **Energy Efficiency**

Relevant NZBC Clause	Product Performance		
Thermal Rating	Not tested		

## X

#### **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3 V:290424

# **Product Information Declaration Shaw Contract Color Frame Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than FE

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Note**

It is expected that **Shaw Contract Color Frame** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:290424

# **Product Information Declaration Shaw Contract Color Frame Range**

#### **Identifiers**

This JPID covers all colours from Shaw Contract Color Frame including:

Impression 11012 Pretend 11011 Vanish 11010 Mojo 11009 Clouded 11007 Disappear 11006 Coax 11005 Crystal 11004 Mystery 11003 Mystic Grey 11002 Mask 11001 Duplicity 11000 Magic 10999 Paradox 10998 Figment 10997 Imply 10996 Charming 10994 Day Dream 10993 Coax Ecologix 11026 Mask Ecologix 11025 Magic Ecologix 11024

Inspire 10992

Imagine 10991 Enchanted 10990 Quirky 10989 Tricky 10987 Frolic 10986 Glowing 10985 Sand 10984 Aurora 11015 Figment Ecologix 11023 Imply Ecologix 11022 Enchanted Ecologix 11021 Quirky Ecologix 11020 Hyper Green Ecologix 11019 Puzzle 11018 Ember 11017 Stunt 11016 Appearance 11014 Blaze 11008 Hyper Blue 10995 Hyper Green 10988 Observe 11013 Utopia 25210

#### **Sustainability**

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	1 Point
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star	Credit 13	1 Point
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		10.7 kg CO2/m2 (Cradle to Gate)

#### **Environmental Credentials**









Declare.













Product Manufacturer: Shaw Contract Country of Origin: United States of America

## **Jacobsen**<sup>®</sup>

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

Page 3 of 3 V:290424