# Jacobsen®

# **Product Information Declaration**

# **Britomart Subway Tile Range**

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the ceramic & porcelain tiles range sold by Jacobsen as **Britomart Subway Tile** 

#### **Scope and Limitations of Intended Use**

~	Residential	~	Commercial
×	High Traffic	×	Low Traffic
×	Antistatic Environment	×	Food Prep Areas
X	Ramp/Entry	×	Under Floor Heating

#### **Identifiers**

See individual sku codes under identifiers

Interior Exposed Sunlight 1 Х Clean Room

**Over Existing Floor** 

Х

Х Exterior

Wet Areas

Х With Wheels

# B

#### **Stability**

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	Suitable
Commercial	-
Industrial	_

#### С **Protection from Fire**

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Naturally Fire Resistant
C4.3 (b) Floor	Naturally Fire Resistant

### D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

# Ε

#### **Moisture**

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

# F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance
F2.3.1	No VOC's
	Does not encourage bacterial growth
_	Phthalate-free
Indoor Air Quality	Optimal

## G **Services and Facilities**

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

## Н **Energy Efficiency**

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

### Χ **Warnings and Bans**

Building Act 2004	Product Performance
Section 26	-

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## **Product Information Declaration Britomart Subway Tile Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

# Note

It is expected that **Britomart Subway Tile** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

## **Product Information Declaration Britomart Subway Tile Range**

#### **Identifiers**

24820

24821

24823

24824

This JPID covers all colours from Britomart Subway Tile including:

Black Gloss Subway 75mm x 300mm Cream Gloss 75mm x 300mm TOU75301/HM75301 Cream Gloss Subway 75mm x 300mm White Gloss 75mm x 300mm TOU75300 or OP011YE Flat White Gloss Subway 75mm x White Matt 75mm x 300mm HM75306 300mm 24822 Flat White Gloss 75mm x 300mm White Gloss Subway 75mm x 300mm TOU75302 Black Gloss 75mm x 300mm White Matt Subway 75mm x 300mm TOU75305/HM75305

#### **Sustainability**

Credit 12 Credit 20	- 1 Point
	1 Point
Credit 21	-
Credit 13	-
Credit 20	1 Point
Credit 21	-
Credit 21	-
HC 7	1 Point
EN 3	-
Mat-1	-
Mat-2	1 Point
ation (EPD)	-
Embodied Carbon Emission Data	
	Credit 20 Credit 21 Credit 21 HC 7 EN 3 Mat-1 Mat-2 ation (EPD)

#### **Environmental Credentials**

# **Jacobsen**<sup>®</sup>

Jacobsen 41D Morrin Road. St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: Tile Depot Country of Origin: China