

## Product Information Declaration

# Audacity Detail Trims Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the laminate range sold by Jacobsen as Audacity Detail Trims

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

|  |   |   |   |
|--|---|---|---|
| <input checked="" type="checkbox"/> Residential            | <input checked="" type="checkbox"/> Commercial          | <input checked="" type="checkbox"/> Interior            | <input checked="" type="checkbox"/> Exterior    |
| <input checked="" type="checkbox"/> High Traffic           | <input checked="" type="checkbox"/> Low-Traffic         | <input checked="" type="checkbox"/> Exposed-Sunlight    | <input checked="" type="checkbox"/> Wet-Areas   |
| <input checked="" type="checkbox"/> Antistatic-Environment | <input checked="" type="checkbox"/> Food-Prep-Areas     | <input checked="" type="checkbox"/> Clean-Room          | <input checked="" type="checkbox"/> With Wheels |
| <input checked="" type="checkbox"/> Ramp/Entry             | <input checked="" type="checkbox"/> Under Floor Heating | <input checked="" type="checkbox"/> Over-Existing-Floor |   |

### B Stability

| Relevant NZBC Clause | Product Performance                                      |
|----------------------|--|
| B2.3.1(c)            | 15 years Limited Residential, 5 years Limited Commercial |
| Residential          | AC4  |
| Commercial           | AC4  |
| Industrial           | -  |

### C Protection from Fire

| Relevant NZBC Clause | Product Performance                         |
|----------------------|---|
| C4.3                 |   |
| C4.3 (a) Wall        | -   |
| C4.3 (b) Floor       | CHF >11 kW/m <sup>2</sup> (ISO 9239.1:2010) |

### D Access

| Relevant NZBC Clause   | Product Performance |
|------------------------|---------------------|
| D1.3.3                 |                     |
| Level Surface (Wet)    | -                   |
| Level Surface (Dry)    | Acceptable Solution |
| Suitable for food prep | -                   |

### E Moisture

| Relevant NZBC Clause | Product Performance           |
|----------------------|-------------------------------|
| E3.3.3               | Impervious and easily cleaned |
| E3.3.5               | Impervious and easily cleaned |
| E3.3.6               | Water resistant               |
| NZBC/AS1             | -                             |

### F Safety of Users

| Relevant NZBC Clause | Product Performance                 |
|----------------------|-------------------------------------|
| F2.3.1               | ≤ 0.5 mg/m <sup>3</sup>             |
|                      | Does not encourage bacterial growth |
|                      | Phthalate-free                      |
| Indoor Air Quality   | Optimal                             |

### G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| G3.3.2 (b)           | Water resistant     |
| G6.3.2               | -                   |

### H Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|---------------------|
| Thermal Rating       | Not tested          |

### X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26        | -                   |

### Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Audacity Detail Trims Range

---

### B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that **Audacity Detail Trims** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Audacity Detail Trims Range

### Identifiers

This JPID covers all colours from Audacity Detail Trims including:

|                                       |  |
|---------------------------------------|--|
| T Mould Victorian Oak 2.4m 22064      | Reducer Castlepoint 2.4m 22097         |
| T Mould Riverton 2.4m 22078           | Reducer American Oak 2.4m 22074        |
| Square Nose Helena Bay 2.4m 22104     | Quarter Round Victorian Oak 2.4m 22160 |
| Square Nose Foxton 2.4m 22113         | Quarter Round Riverton 2.4m 22172      |
| Square Nose Fiordland 2.4m 22119      | Quarter Round Milford 2.4m 22170       |
| Square Nose Eden 2.4m 22109           | Quarter Round Mercury Bay 2.4m 22167   |
| Square Nose Castlepoint 2.4m 22108    | Quarter Round Longwood 2.4m 22161      |
| Square Nose American Oak 2.4m 22105   | Quarter Round London Fog 2.4m 22168    |
| Reducer Victorian Oak 2.4m 22095      | Quarter Round Helena Bay 2.4m 22158    |
| Reducer Riverton 2.4m 22103           | Quarter Round Foxton 2.4m 22169        |
| Reducer Milford 2.4m 22102            | Quarter Round Fiordland 2.4m 22176     |
| Reducer Mercury Bay 2.4m 22099        | Quarter Round Eden 2.4m 22166          |
| Reducer Longwood 2.4m 22096           | Quarter Round Castlepoint 2.4m 22165   |
| Reducer London Fog 2.4m 22100         | Stair Nosing Longwood 2.4m 22120       |
| Reducer Helena Bay 2.4m 22073         | Stair Nosing London Fog 2.4m 22153     |
| Reducer Foxton 2.4m 22101             | Stair Nosing Helena Bay 2.4m 22116     |
| T Mould Milford 2.4m 22077            | Stair Nosing Foxton 2.4m 22155         |
| T Mould Mercury Bay 2.4m 22085        | Stair Nosing Fiordland 2.4m 22175      |
| T Mould Longwood 2.4m 22080           | Stair Nosing Eden 2.4m 22122           |
| T Mould London Fog 2.4m 22086         | Stair Nosing Castlepoint 2.4m 22121    |
| T Mould Helena Bay 2.4m 22062         | Stair Nosing American Oak 2.4m 22088   |
| T Mould Foxton 2.4m 22076             | Square Nose Victorian Oak 2.4m 22106   |
| T Mould Fiordland 2.4m 22081          | Square Nose Riverton 2.4m 22115        |
| T Mould Eden 2.4m 22084               | Square Nose Milford 2.4m 22114         |
| T Mould Castlepoint 2.4m 22083        | Square Nose Mercury Bay 2.4m 22111     |
| T Mould American Oak 2.4m 22063       | Square Nose Longwood 2.4m 22107        |
| Stair Nosing Victorian Oak 2.4m 22089 | Square Nose London Fog 2.4m 22112      |
| Stair Nosing Riverton 2.4m 22157      | Quarter Round American Oak 2.4m 22159  |
| Stair Nosing Milford 2.4m 22156       |  |
| Stair Nosing Mercury Bay 2.4m 22152   |  |
| Reducer Fiordland 2.4m 22118          |  |
| Reducer Eden 2.4m 22098               |  |

### Sustainability

| Rating System                            | Rating    | Product Performance |
|--|-----------|---------------------|
| Green Star Design & As Built NZ (V1)     | Credit 12 | -                   |
|  | Credit 20 | -                   |
|  | Credit 21 | -                   |
| Green Star Interiors NZ (V1)             | Credit 13 | -                   |
|  | Credit 20 | -                   |
|  | Credit 21 | -                   |
| Green Star Performance NZ (V1)           | Credit 21 | -                   |
|  |           |                     |
| Homestar V5                              | HC 7      | 1 Point             |
|  | EN 3      | -                   |
| Homestar V4                              | Mat-1     | -                   |
|  | Mat-2     | 1 Point             |
| Environmental Product Deceleration (EPD) |           | -                   |
| Embodied Carbon Emission Data            |           | -                   |

### Environmental Credentials

Product Manufacturer: China Floors  
Country of Origin: China

# Jacobsen®

Jacobsen 41D Morrin Road,  
St Johns, 1072  
0800 800 460  
[jacobsen.co.nz](http://jacobsen.co.nz)  
[sales@jacobsen.co.nz](mailto:sales@jacobsen.co.nz)

NZBN:  
9429040403328