Product Information Declaration

Audacity Detail Trims Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the laminate range sold by Jacobsen as Audacity Detail Trims

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓	Residential	✓ Commercial ✓ Interior X Exterior	
✓	High Traffic	X Low Traffic X Exposed Sunlight X Wet Areas	
×	Antistatic Environment	X Food Prep Areas X Clean Room V With Wheels	
×	Ramp/Entry	✓ Under Floor Heating X Over Existing Floor	

B

Stability

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	15 years Limited Residential, 5 years Limited Commercial	
Residential	AC4	
Commercial	AC4	
Industrial		

Protection from Fire

Relevant NZBC Clause	Product Performance	
C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	CHF >11 kW/m2 (ISO 9239.1:2010)	

Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	-	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	-	

E

Moisture

Relevant NZBC Clause	Product Performance	
E3.3.3	Impervious and easily cleaned	
E3.3.5	Impervious and easily cleaned	
E3.3.6	Water resistant	
NZBC/AS1	-	

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 0.5 mg/m3
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

Н

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X

Warnings and Bans

Building Act 2004	Product Performance	
Section 26	_	

Supporting Documents

All supporting documents can be found on the Jacobsen website, <u>jacobsen.co.nz</u> or by this QR code



Page 1 of 3

Product Information Declaration Audacity Detail Trims Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Audacity Detail Trims** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:210524

Product Information Declaration Audacity Detail Trims Range

Identifiers

This JPID covers all colours from Audacity Detail Trims including:

T Mould Victorian Oak 2.4m 22064 T Mould Riverton 2.4m 22078 Square Nose Helena Bay 2.4m 22104 Square Nose Foxton 2.4m 22113 Square Nose Fiordland 2.4m 22119 Square Nose Eden 2.4m 22109 Square Nose Castlepoint 2.4m 22108 Square Nose American Oak 2.4m 22105 Reducer Victorian Oak 2.4m 22095 Reducer Riverton 2.4m 22103 Reducer Milford 2.4m 22102 Reducer Mercury Bay 2.4m 22099 Reducer Longwood 2.4m 22096 Reducer London Fog 2.4m 22100 Reducer Helena Bay 2.4m 22073 Reducer Foxton 2.4m 22101 T Mould Milford 2.4m 22077 T Mould Mercury Bay 2.4m 22085 T Mould Longwood 2.4m 22080 T Mould London Fog 2.4m 22086 T Mould Helena Bay 2.4m 22062 T Mould Foxton 2.4m 22076 T Mould Fiordland 2.4m 22081 T Mould Eden 2.4m 22084 T Mould Castlepoint 2.4m 22083 T Mould American Oak 2.4m 22063 Stair Nosing Victorian Oak 2.4m 22089 Stair Nosing Riverton 2.4m 22157 Stair Nosing Milford 2.4m 22156 Stair Nosing Mercury Bay 2.4m 22152 Reducer Fiordland 2.4m 22118 Reducer Eden 2.4m 22098

Quarter Round Victorian Oak 2.4m 22160 Quarter Round Riverton 2.4m 22172 Quarter Round Milford 2.4m 22170 Quarter Round Mercury Bay 2.4m 22167 Quarter Round Longwood 2.4m 22161 Quarter Round London Fog 2.4m 22168 Quarter Round Helena Bay 2.4m 22158 Quarter Round Foxton 2.4m 22169 Quarter Round Fiordland 2.4m 22176 Quarter Round Eden 2.4m 22166 Quarter Round Castlepoint 2.4m 22165 Stair Nosing Longwood 2.4m 22120 Stair Nosing London Fog 2.4m 22153 Stair Nosing Helena Bay 2.4m 22116 Stair Nosing Foxton 2.4m 22155 Stair Nosing Fiordland 2.4m 22175 Stair Nosing Eden 2.4m 22122 Stair Nosing Castlepoint 2.4m 22121 Stair Nosing American Oak 2.4m 22088 Square Nose Victorian Oak 2.4m 22106 Square Nose Riverton 2.4m 22115 Square Nose Milford 2.4m 22114 Square Nose Mercury Bay 2.4m 22111 Square Nose Longwood 2.4m 22107 Square Nose London Fog 2.4m 22112 Quarter Round American Oak 2.4m 22159

Reducer Castlepoint 2.4m 22097

Reducer American Oak 2.4m 22074

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Decele	-	
Embodied Carbon Emission Da	-	

Environmental Credentials

Jacobsen[®]

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: **China Floors**Country of Origin: China

Page 3 of 3 V:210524