Jacobsen[®]

Product Information Declaration

Jacobsen Audacity Laminate Range

Range Description


This Jacobsen Product Information Declaration (PID) applies to the laminate range sold by Jacobsen as Jacobsen Audacity Laminate

Scope and Limitations of Intended Use

•	Residential	~	Commercial
,	High Traffic	×	Low Traffic
(Antistatic Environment	×	Food Prep Ar
ć	Ramp/Entry	~	Under Floor I

Traffic Prep Areas

er Floor Heating



Interior

Х

Х

Exposed Sunlight

Over Existing Floor

Clean Room

X Exterior

> Х Wet Areas

> > With Wheels

B

✓ |✓ |× |× |×

Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	5 Years Commercial Limited, 15 Years Residential Limited
Residential	AC4
Commercial	AC4
Industrial	-

С **Protection from Fire**

Relevant NZBC Clause Product Performance C4.3 C4.3 (a) Wall _ C4.3 (b) Floor > 11 (EN ISO 9239-1:2010)

Π Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

Ε

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

н

Energy Efficiency

Relevant NZBC Clause	Product Performance	
Thermal Rating	Not tested	

F

Х

Safety of Users

Warnings and Bans

Building Act 2004

Section 26

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 0.5mg/m3 (CDPH/ EHLB v1.2-2017)
	Does not encourage bacterial growth
_	Phthalate-free
Indoor Air Quality	Optimal

Product Performance

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration Jacobsen Audacity Laminate Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

Note

It is expected that Jacobsen Audacity Laminate is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Product Information Declaration Jacobsen Audacity Laminate Range

Identifiers

This JPID covers all colours from Jacobsen Audacity Laminate including:

Castle Point 21415 Fiordland 21412 Mercury Bay 21411 Helena Bay 21410 Riverton 21409 Victorian Oak 21404 Milford 21403 American Oak 21402 London Fog 21400 Foxton 21399 Eden 21398 Longwood 21397

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	-
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Decele	-	
Embodied Carbon Emission Data -		

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: China Floors Country of Origin: China