

Product Information Declaration

Elemental XL Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the luxury vinyl tiles (lvt) range sold by Jacobsen as Elemental XL

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

| | | | |
|--------------------------|-----------------------|-----------------------|---------------|
| ✓ Residential | ✓ Commercial | ✓ Interior | ✗ Exterior |
| ✓ High Traffic | ✗ Low Traffic | ✓ Exposed Sunlight | ✓ Wet Areas |
| ✗ Antistatic Environment | ✗ Food Prep Areas | ✗ Clean Room | ✓ With Wheels |
| ✗ Ramp/Entry | ✓ Under Floor Heating | ✓ Over Existing Floor | |

B Stability

| Relevant NZBC Clause | Product Performance |
|----------------------|---|
| B2.3.1(c) | 15 years Commercial, 20 years Residential |
| Residential | 23 Heavy |
| Commercial | 33 Heavy |
| Industrial | 42 General |

C Protection from Fire

| Relevant NZBC Clause | Product Performance |
|----------------------|--------------------------------|
| C4.3 | |
| C4.3 (a) Wall | - |
| C4.3 (b) Floor | CHF 9. kW/m2 (ISO 9239.1:2010) |

D Access

| Relevant NZBC Clause | Product Performance |
|------------------------|-----------------------|
| D1.3.3 | |
| Level Surface (Wet) | SRV 42 (AS 4586:2013) |
| Level Surface (Dry) | Acceptable Solution |
| Suitable for food prep | - |

E Moisture

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------|
| E3.3.3 | Impervious and easily cleaned |
| E3.3.5 | Impervious and easily cleaned |
| E3.3.6 | Water resistant |
| NZBC/AS1 | - |

F Safety of Users

| Relevant NZBC Clause | Product Performance |
|----------------------|-------------------------------------|
| F2.3.1 | ≤ 0.5 mg/m3 |
| | Does not encourage bacterial growth |
| | Phthalate-free |
| Indoor Air Quality | Good |

G Services and Facilities

| Relevant NZBC Clause | Product Performance |
|----------------------|---|
| G3.3.2 (b) | Water resistant |
| G6.3.2 | ΔLW 17dB - 2.5mm with 3mm Regupol Sonus Multi |

H Energy Efficiency

| Relevant NZBC Clause | Product Performance |
|----------------------|----------------------|
| Thermal Rating | 0.01745m2K/W at 10°C |

X Warnings and Bans

| Building Act 2004 | Product Performance |
|-------------------|---------------------|
| Section 26 | - |

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration

Elemental XL Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that Elemental XL is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration Elemental XL Range

Identifiers

This JPID covers all colours from Elemental XL including:

| | |
|---------------------------------|-----------------------------|
| Onega 5.0mm 23030 | Bolsena Chevron 2.5mm 22722 |
| Albano 5.0mm 23029 | Onega 2.5mm 22721 |
| Constance 5.0mm 23028 | Albano 2.5mm 22720 |
| Como 5.0mm 23027 | Constance 2.5mm 22697 |
| Prespa 5.0mm 23026 | Como 2.5mm 22696 |
| Bolsena 5.0mm 23025 | Prespa 2.5mm 22331 |
| Lugano 5.0mm 23024 | Bolsena 2.5mm 22330 |
| Brienz 5.0mm 23023 | Lugano 2.5mm 22329 |
| Maggiore 5.0mm 23022 | Brienz 2.5mm 22328 |
| Lomond 5.0mm 23021 | Maggiore 2.5mm 22327 |
| Bolsena Herringbone 2.5mm 22723 | Lomond 2.5mm 22326 |

Sustainability

| Rating System | Rating | Product Performance |
|---|-----------|--|
| Green Star Design & As Built NZ (V1) | Credit 12 | - |
| | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 0.75 |
| Green Star Interiors NZ (V1) | Credit 13 | - |
| | Credit 20 | 1 Point |
| | Credit 21 | Sustainability Factor (SF) = 0.75 |
| Green Star Performance NZ (V1) | Credit 21 | 1 Point |
| Homestar V5 | HC 7 | 1 Point |
| | EN 3 | 1.25 Points |
| Homestar V4 | Mat-1 | 1.5 Points |
| | Mat-2 | 1 Point |
| Environmental Product Declaration (EPD) | | Yes |
| Embodied Carbon Emission Data | | 8.342 kgCO ₂ eq / m ² (Cradle to Gate) |

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328

Product Manufacturer: Aspecta
Country of Origin: China