Jacobsen®

Product Information Declaration

Trend Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as **Trend**

Scope and Limitations of Intended Use

~	Residential
×	High Traffic
×	Antistatic Environment
X	Ramp/Entry

★ Low Traffic
 ✓ Food Prep Areas
 ✓ Under Floor Heating

X Commercial

✓ Interior
 ✓ Exposed Sunlight
 X Clean Room

Identifiers

See individual sku codes under identifiers

X Over Existing Floor

- X Exterior
- ✓ Wet Areas
- With Wheels

B Stability

-	
Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years Residential
Residential	22/23 Heavy Duty
Commercial	31 General
Industrial	-

C Protection from Fire

Relevant NZBC Clause	Product Performance	
C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	6.2 kW/m2 (ISO 9239.1:2010)	

D Access

G

G3.3.2 (b)

G6.3.2

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

Product Performance

16 or 17 dB (ISO 717/2)

Water resistant

Ε

Moisture

Relevant NZBC Clause	Product Performance	
E3.3.3	Impervious and easily cleaned	
E3.3.5	Impervious and easily cleaned	
E3.3.6	Water resistant	
NZBC/AS1	-	

F

Safety of Users

Relevant NZBC Clause	Product Performance	
F2.3.1	Gold,≤ 100µg/m3 (EN 16516)	
	Does not encourage bacterial growth	
	Phthalate-free	
Indoor Air Quality	Optimal	

H Energy Efficiency

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.03 m ² •K/W (ISO 10456)

X Warnings and Bans

Building Act 2004 Product Performance
Section 26 -

Services and Facilities

Relevant NZBC Clause

Supporting Documents All supporting documents can be found on the

Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration Trend Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

Note

It is expected that **Trend** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Product Information Declaration Trend Range

Identifiers

This JPID covers all colours from Trend including:

Swan Dark Brown 19201

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	_
	Credit 21	Sustainability Factor (SF) = 1
Green Star	Credit 13	_
Interiors NZ (V1)	Credit 20	_
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		5.50 kgCO2e / m2 (Cradle to Gate)

Environmental Credentials



Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328



Product Manufacturer: Tarkett Country of Origin: Germany