Product Information Declaration

Tarkett Primo Premium Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as **Tarkett Primo Premium**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

✓	Residential
$\overline{}$	

High Traffic

Antistatic Environment

X Ramp/Entry

Commercial

X Low Traffic

✓ Food Prep Areas

Under Floor Heating

Interior

✓ Exposed Sunlight

✓ Clean Room

X Over Existing Floor

Exterior

✓ Wet Areas

✓ With Wheels

R

Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	23 (ISO 10874)
Commercial	34 (ISO 18074)
Industrial	43 (ISO 18074)

Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	Group 3 (ISO 5660.1-2015)
C4.3 (b) Floor	CRF 10kW/m2 , (ISO 9239-1:2010)

D

Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	SRV 53 (AS 4586:2013)
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

Ε

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10¬μg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G

Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

Н

Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.01m2 K/W (EN 12667)

X

Warnings and Bans

Building Act 2004	Product Performance
Section 26	_

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:280424

Product Information Declaration Tarkett Primo Premium Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Primo Premium** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:280424

Product Information Declaration Tarkett Primo Premium Range

Identifiers

This JPID covers all colours from Tarkett Primo Premium including:

Light Green 12549 Clay Grey E21010625 Medium Warm Grey E21010600 Light Beige 12548 Dark Cool Beige 12547 Light Cool Beige 12546 Dark Cool Grey 12545 Medium Cool Grey 12544 Light Warm Grey 12543 Medium Grey 12542 Medium Pure Grey 12541 Soft Red E21010668 Soft Orange 21319 Dark Blue 12540 Medium Blue 12539 Soft Yellow E21010664 Soft Purple 21973 Light Yellow 21318

Dark Warm Beige 12538 Medium Warm Beige 12537 Medium Cool Beige 12536 Dark Warm Grey 12535 Medium Grey Beige 12534 Black 12533 Light Blue 12551 Dark Green 12550 Medium Green 21330 Light Red 12532 Grey 12531 Light Pure Grey 12530 Dark Orange 19107 White Olive Green 23078 Sky Blue 21317 Dark Brick Grey E21010632 Sand 21117

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product D	eceleration (EPD)	Yes
Embodied Carbon Emiss	ion Data	5.71 kgCO2e / m2 (Cradle to Gate)

Environmental Credentials























Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

© Tarkett

Product Manufacturer: **Tarkett** Country of Origin: Sweden

Page 3 of 3 V:280424