

AQUARELLE WALL HFS

Heterogeneous vinyl wall covering

Waterproof vinyl wall covering for bathrooms and wet areas

Wall protection for heavy duty commercial wet room areas, in designer ranges to coordinate with safety and wet area floors.

WATERPROOF	LOWEST VOC	HIGH FIRE RESISTANCE
<p>Wet Area Walls</p> <p>Additional waterproofing / tanking membrane not required. PU Shield provides an easy clean, abrasion resistant surface.</p>	<p>Optimal Indoor Air</p> <p>Phthalate free, with VOC emissions below quantifiable levels, giving the best quality indoor environment.</p>	<p>Group 1</p> <p>Provides a high level of fire resistance, suitable for all areas (sprinklered).</p>

Product Characteristics	Standard	Aquarelle Wall HFS
Product construction	EN 649	Heterogeneous vinyl wall covering
Classification	EN 259	Heavy duty
Total thickness	ISO 24346 (EN 428)	0.92mm
Wear layer thickness	ISO 24340 (EN 429)	0.12mm
Total weight	ISO 23997 (EN 430)	1500 g/m ²
Form of delivery	EN 426	Approx. 35 Lm x 2 m
Warranty		10 years
Available colours		32

Performance Characteristics	Standard	Aquarelle Wall HFS
Dimensional stability	ISO 23999 (EN 434)	Length: ≤ 0.80% Width: ≤ 0.40%
Reaction to fire	AS 3837	Group 1 Average extinction area 469.4m ² /kg
Total VOC emissions	AgBB/DIBt	≤ 10 µg/m ³ (after 28 days)
Acoustic absorption	NF EN ISO 354	0.05 (H)
Chemical resistance	ISO 26987 (EN 423)	Good resistance
Hygiene	-	Does not contribute to infection spreading
Seam strength	EN 684	≥ 150 N/50mm