

LokWorx is a pressure sensitive adhesive for the installation of EcoWorx carpet tile. This non-toxic and odorless system provides an alternative to wet adhesive, virtually eliminating the issue of VOCs (Volatile Organic Compounds), and provides ease and versatility of installation.

LokWorx can be applied to the corner of a tile for floating or center applied and adhered to the floor for attached installations.

The box serves as the dispenser making LokWorx easy to store, maintain and use. Floor preparation is limited to smoothing floor and clearing dust and debris.



## Features

- Non-Toxic and odorless system provides an alternative to wet adhesive.
- LokWorx can be applied to the corner of a tile for floating installations or center applied and adhered to the floor for attached installations.
- Can be installed over concrete, VCT, VAT, cutback adhesive, raised access floors, pressure sensitive and multipurpose adhesive, wood and finished hardwood.
- Lokworx can easily be removed.

## Suggested Applications

- Corporate
- K-12 and Higher Ed
- Multi Family
- Student Housing
- Military Housing

Every installation is unique. Contact your local account manager for specific site requirements.



## Product Specifications

|                    |   |
|--------------------|---|
| Style Information  | Lokworx Box 500 adhesive squares on a roll<br>Lokworx Case 10 boxes of 500 adhesive squares on each roll                            |
| Packaging          | Unlimited shelf life<br>Store under 120 degrees   |
| Moisture Level     | Up to 5 pounds alkalinity and 85% RH in subfloor and up to 12 pH in subfloor concrete   |
| Approved Subfloors | VCT, VAT, terrazzo, raised access floors, finished hardwood, wood, cutback, pressure sensitive and multi-purpose adhesive, concrete |
| Floor Prep         | level and clean<br>refer to full installation guidelines for more information   |
| VOCs               | VOC free-CRI Green Label Plus Certified   |

|  | Application   | Tabs required per tile box |
|--|---|----------------------------|
| Adhered Application  | apply 1 square per 24x24 in the center of the tile  | 12                         |
|  | apply 2 squares per 18x36 in the center of the tile   | 20                         |
|  | apply 2 squares per 9x36 in the center of the tile  | 40                         |
|  | apply 3 squares per 12x48 in the center of the tile   | 36                         |
|  | apply 1 square per hexagon in the center of the tile  | 12                         |
|  | apply 1 square rhombus in the center of the tile  | 16                         |
|  | <i>Installations will require extra LokWorx for perimeter tiles. Installations must be rolled with 75lb roller.</i> |                            |
| Floating Application   | apply 1/4 square to corner of 24x24 in tile   | 12                         |
|  | apply 1/4 squares to 4 corners and 1/2 square per long side of 18x36 tile   | 20                         |
|  | apply 1/4 squares to 4 corners and 1/2 square per long side of 9x36 tile  | 40                         |
|  | apply 1/4 squares to 4 corners and 1/2 square per length of 12x48 tile  | 36                         |
|  | apply 1/4 square to 4 corners of hexagon tile   | 12                         |
|  | apply 1/4 square to 4 corners of rhombus tile   | 16                         |
| <i>Perimeter of floating installation must be secured. An additional 25% LokWorx tabs should be ordered to account for perimeter cut tiles, site layout and tiles shapes / sizes. Installations must be rolled with 75 lb. roller.</i> |   |                            |