








Specifications


| | | | | |
|--|---|---|---|---|
| Construction | Multi-level Pattern loop | | | |
| Fibre | Eco Solution Q™ Nylon | | | |
| Dye Method | 100% Solution Dyed | | | |
| Pattern Repeat | None | | | |
| Tufted Weight | 17oz | | | |
| Gauge | 1/12" | | | |
| Finished Pile Thickness | 2.18mm | | | |
| Total Thickness | 5.82mm | | | |
| Product Size | 610mm x 610mm | | | |
| Primary Backing | Synthetic | | | |
| Secondary Backing | Ecoworx™ tile | | | |
| Protective Treatments | SSP® Shaw Soil Protection | | | |
| ISO 9239.1: 2010 Fire Test | Mean Critical Radiant Flux 8.5kW/m ² | | | |
| Electrostatic Propensity | Less than 3.5 kv | | | |
| Warranty | Lifetime Commercial Limited | | | |
| Environmental | Good Environmental Choice Australia Cradle to Cradle Silver Certified Declare Label - LBC Compliant | | | |
| Recyclability | 100% recyclable | | | |
| Materials | Does not contain PVC, Phthalates, or PBD/PBDE | | | |
| Recycled Content: | | | | |
| - Total Recycled Content by Weight | 45% | | | |
| - Pre-consumer | 45% | | | |
| - Post-consumer | - | | | |
| Installation Options | | | | |
|  |  |  |  |  |
| quarter turn | monolithic | brick | random | ashlar |



Sea Adventure



Sea Edge Adventure Green



Sea Edge Adventure Yellow



Sea Edge Adventure Teal

