



Silent Shield

Regupol 4515

<b>Recommended for use under</b>		Laminate Engineered Wood		Laminate Engineered Wood Homogeneous Vinyl Sheet (4515-S) Ceramic Tiles Glue Down LVT	
<b>Material</b>		Crosslinked polymeric foam with polymeric film		PUR foam and cork, bound with polyurethane	
<b>Thickness</b>		2mm		4.5mm (4515-S; 3mm)	
<b>Width</b>		1000mm		1000mm	
<b>Roll Length</b>		30m		20m	
<b>Application</b>		Residential, Commercial		Residential, Commercial	
<b>Installation</b>		Floating only		Floating or Glue down	
<b>Environmental</b>		-		Good Environmental Choice Australia ISO14001 PVC free	
<b>Approximate acoustic dB reduction (compared to bare concrete floor)</b>	<b>12.5mm Wood</b>	-		-	
	<b>14mm Wood</b>	-		with Regupol 4.5mm	17 dB
	<b>8mm Laminate</b>	with Silent Shield	18 dB	with Regupol 4.5mm	19 dB
	<b>2mm Vinyl Sheet</b>	-		with Regupol 4515-S 3mm	17 dB
	<b>10mm Ceramic Tile</b>	-		with Regupol 4.5mm	17 dB
	<b>2mm LVT</b>	-		with Regupol 4515-S 3mm	18 dB

Refer to [www.jacobsens.co.nz/downloads/accessories](http://www.jacobsens.co.nz/downloads/accessories) for full test results.

**Jacobsen®**

[www.jacobsens.co.nz](http://www.jacobsens.co.nz)